





01-08

01
03
05
07
09
11

13-25

13 MIPC1000-80T
15 MPS10020KT-C
17 MPS20020KT-C
19 MIPC1000-100
21 MIPC1000-100C2
23 MIPC1000-160L
25 MIPC1000-135C1

27-29

27 CCU
28 TCU
29 PLC

30

31-32



150~1000 V



OTA



180 kW



150~1000 V




OTA



180 kW

120 kW




323~456 VAC
380 VAC
50 Hz
≥ 0.99
3W + N + PE
120 kW
150~1000 VDC
300~1000 VDC
≤ ±0.5%
≤ ±1%
≥ 94%
≤ 65 dB
-20 °C ~ +55 °C
-40 °C ~ +75 °C
5~95%
≤ 0.01% / °C 0.01% / °C <
CAN
700 x 1700 x 460 (mm)
IP54
5 m

240 kW



150-1000 V

OTA



600 kW



OTA



v

323~456 VAC			
380 VAC			
50 Hz			
≥ 0.99			
3W + N + PE			
600 kW			
150~1000 VDC			
300~1000 VDC			
250 A		600 A	
()	12 (	10	2)
≥ 94%			
≤ 65 dB			
-20 °C ~ +55 °C			
-40 °C ~ +75 °C			
5~95%			
≤ 3000 m		≤ 10000 m	<
CAN			
4G / WIFI			
2		1	
IP	IP55		
5 m / 3.5 m			

ف


Θ

Ř

ε



MIPC1000-80T





MPS20020KT-C



MIPC1000-100


MIPC1000-100G CE
MIPC1000-100G1 UL



30 kW


MIPC1000-100C2






40 kW

MIPC1000-135C1





(PLC



PLC

- CCS, CHAdEMO()
 - CCS DIN 70121, ISO15118
 - CHAdEMO , 2.0 ()
 - IEC 61851-2:2023
 - ()
- ,
 - CAN ,
 - RS232 , ,
 - Proxima Detection(PD)
 - EIM, PnC

CCS, CHAdEMO 2.0 (Optional)

12 / 24 VDC
9~26 VDC

2 W for CCS, Max. 40 W for CHAdEMO

CAN, RS232

119 x 229 (mm)

-40 °C ~ +85 °C

R&D

>3000

35%

1990

2024 400+

&
32

9

38

28



CNAS TÜV UL-WTDP UL-CTF



